

ΓΕΦΥΡΑ ΡΙΟΥ-ΑΝΤΙΡΡΙΟΥ «ΧΑΡΙΛΑΟΣ ΤΡΙΚΟΥΠΗΣ»

21 ΧΡΟΝΙΑ
ΥΠΟΔΕΙΓΜΑΤΙΚΗΣ
ΛΕΙΤΟΥΡΓΙΑΣ &
ΣΥΝΤΗΡΗΣΗΣ


**RiO-ANTiRRIo
BRiDGE**

POWERED BY  VINCI
HIGHWAYS

11.12.2025



Panos LOUKAS, CEO, GEFYRA SA
Aris STATHOPOULOS VLAMIS, CTO, GEFYRA SA

DISCLAIMER

This presentation is the intellectual property of GEFYRA SA. It is intended solely for the use of the intended audience. No part of this presentation may be copied, shared, distributed, reproduced, or used in any form without the express prior written consent of the author. Unauthorized use, disclosure, or duplication is strictly prohibited.



Geography

Γεωγραφία

History

Ιστορία

Idea

Ιδέα

Chronology

Χρονολόγιο

Metron

Μέτρον

Symmetry

Συμμετρία

EUREKA

 **RIO-ANTIRRIO
BRIDGE**

POWERED BY  **VINCI**
HIGHWAYS

THE GREEK INFRASTRUCTURES BEFORE THE CONCESSIONS ERA



The life before the Bridge (just until before 21 years)



- Ferry monopoly situation (level of service & tariffs)



- 45 min to cross the strait with the Ferry (subject to...)



- In case of bad weather, ferry operation suspension



- Heavy traffic jams in holidays, etc.




- Ambulance Service dependence on Ferries operation, even for life-threatening situations



Rio – Antirrio Bridge

Turning the vision into reality




**RIO-ANTIRRIO
BRIDGE**

Rio – Antirrio Bridge

The success of the Concession Model in Greece



- 42-Year Concession term (1997 – 2039)
- 7 years for Design & Construction (1997 -2004)
- Successful long-term Partnerships:
 - CJV led by VINCI with the participation of Greek Contractors
 - GEFYRA SA Shareholders (2023): VINCI Concessions 72,3% and AKTOR Concessions 27,7%
- 9 International Awards by the scientific community
- Investment: €786M (1997)
- Loan:
 - Lender: EIB (370M€)
 - Debt Repayment ends in 2030



12.08.2004: OPENING OF THE BRIDGE



13.08.2004



GREEK MOTORWAYS NETWORK




POSITIVE MOBILITY
Driving regional growth



Καινοτόμες Μέθοδοι Παρακολούθησης &
Συντήρησης Ειδικών Γεφυρών
Η Περίπτωση της Γέφυρας Ρίου-Αντιρρίου
«Χαρίλαος Τρικούπης»

Innovative Monitoring and Maintenance of
Major Bridges
The Rion-Antirion Bridge “Charilaos
Trikoupis” Case Study




**RIO-ANTIRRIO
BRIDGE**


POWERED BY  VINCI
HIGHWAYS

RION – ANTIRION BRIDGE PROJECT DESCRIPTION (1/5)

Environmental Conditions

Weak Sea Bed

No bedrock encountered in first 100 m during soil investigations, while geological studies indicated similar conditions for up to 500 m.




Water depth up to 65 m

Uniform sea bed at depth of 60 m with steep slopes near coast.

High Seismicity & Tectonic movements

Active normal faults on both sides of Corinthian gulf, at the vicinity of Bridge while the tectonic kinematic of area indicates separation of Peloponnese from mainland Greece with rate of ~15 mm/year.



Strong Wind Area

Due to morphology of surrounding mountains, Rion-Antirion strait is prone to the frequent & strong winds with the most frequent winds to have direction perpendicular to Bridge axis.

Corrosivity

Environment Corrosivity Classified C5-M (ISO 12944).

Navigation channel

Significant marine traffic through Rion – Antirion strait.





RION - ANTIRION BRIDGE PROJECT DESCRIPTION (2/5)

Structural Design -Design Loads & Requirements


Seismic loads

- Seismic design load (Spectrum: pga 0.48 g, max Sa 1.20 g for T=0.2 up to 1.0 sec) - EQ with 2000 years Return Period.
- Tectonic movements:
 - Up to 2m (between adjacent piers) as separate load
 - Up to 1m (between adjacent piers) when combined with specified EQ








RION – ANTIRION BRIDGE PROJECT DESCRIPTION (3/5)

Main Bridge - Structural Features - Overview




RION - ANTIRION BRIDGE PROJECT DESCRIPTION (4/5)

Design Performance-Seismic Design Concept




Mander et al. Model



RION – ANTIRION BRIDGE PROJECT DESCRIPTION (5/5)

Main Bridge – Construction stages



ASSET MANAGEMENT

Technical department Scope of Works

Inspected Assets

 **Concrete Surface:** **190.000m²**

Steel structure surface:
125.000m²

368 Cable Stays
Including steel stands with total length
3.212 km
(half of Earth radius) 

 **238.330** pre-loaded deck bolts

Pavement Surface 
75.400m²

 **208** Cable Stays
Dampers

 **Lightning Protection**
13.900 m stainless steel strand

Monitoring	Maintenance	Special Events Structural Management	Other
Visual Monitoring (inspections)	Regular Maintenance (Planned)	Earthquake	Additional works
Material Monitoring	Corrective/Heavy Maintenance	Strong wind	Technical Improvement works
Instrumented Monitoring Structural monitoring system (permanent) Geometrical monitoring		Fire	Remedial works
		Ship collision	Other administrative/ engineering support
		Major accident	

Monitoring & Maintenance

> 750 inspections → **104.400** photos



>1.100 Maintenance campaigns have been registered

Photos have been logged and linked to the respective bridge elements & campaigns

Resources

Total (including works with Regular Access & special access means)

>890.000 hours




Alpinists

>34.000 hours in air



U/W & Marine access (including divers)
>11.000 hours on & in water

ASSET MANAGEMENT MONITORING & MAINTENANCE INTERACTION



ASSET MANAGEMENT VISUAL & MATERIAL MONITORING: PROCESS OVERVIEW AND MAIN FEATURES

Background - Feedback - Data - Resources


- IMM prepared by Constructor (define visual monitoring content and frequency)-updated upon technical advances and experience
- Concession Perion VM program
- Construction data (WMS, REC, NCRs, etc.)
- Access Means

VM & material testing frequency table for structural elements/equipment

Element	Remarks	Access	Annual	2 Yrs	4 Yrs	5 Yrs	8 Yrs	15 Yrs	20 Yrs
Concrete	Air exp	Regular/Rope	25%						
	Splash	U/W							
	immersed	U/W							
Steel	MB	Regular	100%						
	RAV	Rope or NP/AWP		100%					
Cable Stays	Free length	Rope	25%						
	anchorage	Regular	50%						
	Specialized	Regular			10%				
Scour Protection		U/W							
									100%
Structural Equipment	EJ MB	Rope/AWP	100%						
	EJ AV	Regular		100%					
	IDS MB	Reg/AWP	50%						
	IDS AV	Rope/AWP		100%					
Material	Concrete	Regular					test		
	Cable Stays	-							
	Pavement	-		test				test	

VM main features:

- Fully computerized inspections except for specialized means (rope, underwater, supplier)
- Defect Library set up in IMM & populated continuously
- Breakdown of structures into simple elements (5713)
- Simplified ASB drawings for finding location & developed views of all surfaces
- More than 110 types of inspection forms
- >95.000 photos since 2004





ASSET MANAGEMENT



Material Monitoring: Concrete Durability





Sacrificial concrete block at P2 of Rion Approach Viaduct for concrete durability monitoring



- Measurement of total and free chlorides contents as a function of the depth (from the face of the concrete to 80mm).
- Determination of the chloride diffusion coefficient.
- Life cycle assessment: Simulation through LERM model to assess the free chlorides content at 75mm depth at 120 years.



ASSET MANAGEMENT INSTRUMENTED MONITORING: SHM-OVERVIEW



Designed and installed during construction period (temporary/permanent instrumentation)

Design based on risk assessment analysis with main objectives:



- Characterization of excitation loads (Earthquake/ Wind/Traffic/Thermal)
- Measuring Bridge Response
- Design verification and feedback
- Provide real time alerts and notification based on configurable parameters
- Assist on operation/enhance user safety (black ice risk/strong winds/seismic events)

Operated since 2004 (2005-2024 average overall uptime > 98%)

ASSET MANAGEMENT INSTRUMENTED MONITORING: SHM – OUTPUT & REGURAL ANALYSIS





History Files analysis

- Slow varying processes/statistical parameters of structural response
- History files: 1 value every 30 sec



Dynamic Files Analysis

- Dynamic process/actual measurements of structural response
- Dynamic files: High frequency (100 Hz) records of limited duration (typically 3 sec)





ASSET MANAGEMENT

Instrumented Monitoring - Seismic event follow-up

Automated Event Management (Smart Monitoring)

1. Automated detection of earthquake events
2. Classification of structural response
3. Proposed decision on traffic management (Real time)
4. Automated report preparation and transmission




ASSET MANAGEMENT INSTRUMENTED MONITORING: GEOMETRICAL MONITORING

Measurements and evaluation of:


- Automated detection of earthquake events
- Tectonic movements
- Piers tilt & settlement
- Deck geometry
- TP settlement

The processed data are analyzed & compared with theoretical results




+ ZERO POINT 2004
 * CAMPAIGN 2006
 x CAMPAIGN 2008 Before Earthquake June 8
 r CAMPAIGN 2008 After Earthquake June 8
 o CAMPAIGN 2010
 x CAMPAIGN 2011
 + CAMPAIGN 2016

Scale for displacements :
1 square = 50 x 50 mm



Visual & Instrumented Monitoring, HM & SPECIAL EVENTS: CASE STUDIES



ASSET MANAGEMENT

Visual Monitoring: Underwater inspections case study (1/4)

Scope of Works

- Concrete inspections (e.g. cracks width up to 0,3mm) on the splash zone (from 0 (MSL) to -5m), being an area of 425m² per pier
- Check of Earthing System termination at sea
- Check for scouring around pier footing (perimetry of ~285m per pier)

Challenges

- Removal of substantial marine growth from concrete surfaces (Splash zone)
- Weather conditions (waves)
- Strong currents
- Water depth of scour protection
- High turbidity
- Obstacles (fishing nets)



ASSET MANAGEMENT




Visual Monitoring: Underwater inspections case study (2/4)

Scope of Works

- Concrete inspections (e.g. cracks width up to 0,3mm) on the splash zone (from 0 (MSL) to -5m), being an area of 425m² per pier
- Check of Earthing System termination at sea
- Check for scouring around pier footing (perimetry of ~285m per pier)

Challenges

- Removal of substantial marine growth from concrete surfaces (Splash zone)
- Weather conditions (waves)
- Strong currents
- Water depth of scour protection
- High turbidity
- Obstacles (fishing nets)





ASSET MANAGEMENT

Visual Monitoring: Underwater inspections case study (3/4)

Means for Underwater Inspections in 2008

- Divers for splash and tidal zone
- ROV equipped with a local U/W positioning system based on USBL. The system was operating using specific CAD software that allowed real time position tracking.






ASSET MANAGEMENT

Visual Monitoring: Underwater inspections case study (4/4)

Means for Underwater Inspections in 2018-2020

- Divers for splash and tidal zone
- Multi-beam echosounder (MBES) for bathymetry survey
- Photogrammetric method for scour protection w AI driven intelligent data collection system. Real time photogrammetric model creation




ASSET MANAGEMENT

Instrumented (Geometrical) Monitoring -Offshore piers settlement case study


Measurements and evaluation of:

- Tectonic movements
- **Piers tilt & settlement**
- Deck geometry


The processed data are analyzed & compared with theoretical results




PIER M1
Load-Settlement curves from placing




PIER M4
Load-Settlement curves from placing





SPECIAL EVENT: WIND STORM JAN 23, 2006



● ● ● Evaluation of Bridge response (Strong wind event)




● ● ● Analysis of actual data for required additional damping (CSTB)



SPECIAL EVENT: WIND STORM/EHD SYSTEM PERFORMANCE EVALUATION




Eastern winds
0° from deck axis
maximum wind
speed
(10' average)
m/sec M1M2
m/sec M3M4




MAR 08, 2010


- Eastern winds
~100° from deck axis
- Maximum wind
speed
(10' average)
35.4 m/sec M1M2
30.7 m/sec M3M4



● ● ● Evaluation of Bridge response (Strong wind event)





● ● ● Evaluation of Bridge response (after improvement works)



SPECIAL EVENT: EARTHQUAKE JUN 08, 2008

- Magnitude $M_w=6.4$
- 36km from Rion-Antirion site.
- Focal depth:31km
- Max PGA recorded from on-shore accelerometers:0.127g (at Rion bank)




SPECIAL EVENT: EARTHQUAKE

JUN 08, 2008

	Level 1 Inspection	Level 2 Inspection	Level 3 Inspection	Level 4 Inspection & geometric control	Final step Remedial works
Elapsed time	15 min	4 hours	2 days	2 months	5 months
Inspector	On duty Officer (non technical)	Trained structural inspectors	Trained structural inspectors	Trained structural inspectors and specialized suppliers	
Findings	No findings	Sign of movement on fuses (Pylon)	Minor non structural damage	Minor non structural damage	

Monitoring Report

First review of monitoring data recorded
SLS was not exceeded
Indication of deck release (fuses)



Analysis of Monitoring data

Expertise analysis on collected data

Evaluation of similar EQ's return period
T= 80 to 120 years



Deck re-alignment and fuse replacement





21 years
of exemplary operation and maintenance
21 years
contribution to the sustainable development
of Western Greece

 **RIO-ANTIRRIO
BRIDGE**
POWERED BY 



ΣΑΣ ΕΥΧΑΡΙΣΤΟΥΜΕ

 **RIO-ANTIRRIO
BRIDGE**

POWERED BY  **VINCI
HIGHWAYS**